



Dedicated to the preservation and performance of the  
'89 to '95 Ford Thunderbird Super Coupe and '89 & '90 Mercury Cougar XR7

## LITERATURE

- Home
- Join
- Club Info
- Chargin' Thunder
- Discounts
- SC of the Month
- Members
- Events
- Forums
- Classifieds
- Apparel
- FAQs
- SC Literature
- Multimedia
- Top SCs
- Chapters
- Links
- Chat
- Contact Us
- About This Site
- Disclaimer

### Super Coupe Club of America > SC Literature > Wheel Alignment Specifications for the 1993 SC

submitted by Steve Schecter  
schecter@cox.net

#### Wheel Specs

##### Front End:

Camber	0.00° + or - 0.75°
Caster	+5.50° + or - 0.75°
Toe-In inches (total)	+0.075" + 0.126"
Toe-In Degrees (total)	+0.15° + 0.25°

##### Front Wheel Turning Angle

Full Turn Inside/Outside	20.00°/19.73°
Front Axle Hub Nut Torque	189-254 Lb-Ft

##### Rear End:

Camber	-0.50° + 0.50°
Toe-In inches (total)	+0.060" + or - 0.126"
Toe-In Degrees (total)	+0.12° + 0.25°

**Info Source:** Technical Publication Department Ford Parts and Service Division